

# Steel Commercial Circulating Pedestal Fan 30 In. Black/Silver

**MODEL CCRF-30-P**

Facilities Maintenance / Commercial Circulator Fans



## PRODUCT OVERVIEW

The two speed commercial circulating is perfect for a variety of industries. The pull chain switch give the user functional control. These portable blowers do not have a totally enclosed motor. The guard is coated steel with retaining clips. The fan has a steel hub and aluminum paddle blades. The motor is permanently lubricated with a permanent split capacitor.

## KEY FEATURES

- Meets OSHA standards and is UL C/US listed
- Three blade design keeps are moving
- Use in a clean and dry commercial application
- Wide circular pedestal base

## CORE PRODUCT DATA

ASSEMBLED WEIGHT  
**66 lbs**

ASSEMBLED SIZE  
**27" W x 32.5" L x 106" H**

SHIP WEIGHT  
**66 lbs**

PACKAGE 1 SIZE  
**8" W x 33" D x 33" H**

COLOR / FINISH  
**Black / Silver**

FREIGHT TYPE  
**Parcel**

**AVAILABILITY** Quote Required - Please Contact Sales

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

**QUICKSHIP: --**

PRODUCT SPECIFICATIONS

|                             |                 |
|-----------------------------|-----------------|
| Blade Diameter (in.)        | 30              |
| Mounting Style              | Pedestal        |
| Amps High                   | 2.4             |
| CFM High                    | 6000            |
| CFM Low                     | 4800            |
| Electric Motor Horsepower   | 1/4             |
| Conductor Cord Length (in.) | 108             |
| Conductor Cord              | SJT type 3      |
| Voltage/Phase               | 115V/1PH        |
| CFM Medium                  | 5500            |
| OSHA                        | 1910.212 (a)(5) |
| Lowest Pole Position (in.)  | 43              |
| Highest Pole Position (in.) | 6               |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Gary, TN 37615

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA