

Steel Portable Lift Table 12 Volt DC Powered 36 In. x 48 In. 3000 Lb. Capacity Blue

MODEL EHLTP-3648-3-48-D2

Ergonomic Solutions / Portable Electric Hydraulic Lift Table



PRODUCT OVERVIEW

An electric hydraulic lift table is one of the most efficient ways to raise and lower heavy equipment, and now, it's even better. With the addition of smooth rolling casters, the lift table is now easily portable to different areas and across a variety of surfaces. A removable handle for simple maneuvering is also included to enhance the workability of the unit. The casters and handle make a once steel constructed stationary unit accessible throughout the entire workplace.

KEY FEATURES

- Adjustable travel limit switch
- Hand pendent included to keep a safe distance during use
- Electric toe guard included for pinch point safety
- Emergency safety-stop to ensure user protection

CORE PRODUCT DATA

ASSEMBLED WEIGHT
1051 lbs

ASSEMBLED SIZE
36.375" W x 66.8125" L x 36.5625" H

SHIP WEIGHT
1031 lbs

PACKAGE 1 SIZE
43" W x 68" D x 27" H

COLOR / FINISH
Blue

FREIGHT TYPE
LTL Palletized

AVAILABILITY Out of Stock - Please Contact Sales

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	3,000
Power	12V DC
Platform Width (in.)	36-3/8
Platform Length (in.)	48-3/8
Service Range (in.)	13 to 48
Fork Pocket Width/Height (in.)	7-1/2 x 2-1/2
Fork Pocket Center (in.)	27
Caster Qty./Type	(2) Swivel w/ Brake, (2) Rigid
Caster Diameter/Width (in.)	4 x 2
Caster Material	Glass Filled Nylon
Handle Height (in.)	36-9/16
Battery Depth	8
Battery Width	12
Battery Height	7
Battery Weight	48
Battery Freight Class	60
Battery NMFC Number	60700
Battery NMFC Description	Gel batteries on unit
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1441>