

Steel Dual Power Tote Lifter Charger 67 In. x 26-3/4 In. x 50-1/2 In. 2200 Lb. Capacity Blue

MODEL L-270-DP-HD

Ergonomic Solutions / Dual Power Tote Lifter



PRODUCT OVERVIEW

The tote lifter is designed to lift open bottom skids, boxes, and baskets. Lifter is DC power with rocker switch to raise or lower. This DC powered unit includes an on-board battery charger. The side stabilizers lock lift in place when load is raised over a certain height.

KEY FEATURES

- Solid steel construction provides long lasting rugged use
- Automatic stabilizers engage when forks reach specific height
- Stabilizers design prevent unit from moving
- Front rollers and two rear swivel casters allow for easy portability

CORE PRODUCT DATA

ASSEMBLED WEIGHT
328 lbs

ASSEMBLED SIZE
26.75" W x 67" L x 50.5" H

SHIP WEIGHT
428 lbs

PACKAGE 1 SIZE
48" W x 75" D x 59" H

COLOR / FINISH
Blue

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: YES

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	2,200
Dual Operation	Hand Pump/12 Volt DC Power
Maximum Amperage	140
Side Stabilizer Locks at Raised Height (in.)	15-3/4
Fork Width (in.)	26-3/4
Fork Length (in.)	47
Fork Height (in.)	2
Single Fork Width (in.)	6-1/2
Lowered Height (in.)	3-11/32
Raised Height (in.)	31
Front Roller Diameter (in.)	3
Front Roller Wheel Width (in.)	3
Back Wheel Diameter (in.)	7
Back Wheel Width (in.)	2
Back Wheel Material	Poly-On-Steel
Handle Length (in.)	30
Handle Material	Steel/Plastic
Handle Height (in.)	50-1/2
Handle Width (in.)	14
Overall Maximum Height (in.)	64-1/4
Battery Depth	10
Battery Width	7
Battery Height	11
Battery Weight	44
Battery Freight Class	60
Battery NMFC Number	60700
Battery NMFC Description	Gel batteries on unit
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA