

Steel Folding Mezzanine Ladder 60 In. Mezzanine Height 24-1/4 In. Step Width 350 Lb. Capacity Blue

MODEL LAD-FM-60

Industrial Ladders / Mezzanine Ladders (face mounted/retractable)



PRODUCT OVERVIEW

The mezzanine ladders are used for infrequent usage to access mezzanines. They are ratcheted into climbing angle and back into stored position. The wheels roll on the ground when ratcheted and the handrails mechanically rise into climb position when ladder locks into position. Quickly extend and retract the ladder. The mezzanine ladder allows for quick installation with mounting bracket provided for bolt-on installation or welded installation. Customer must provide their mezzanine height at time of purchase. Baked-in powder-coated toughness. Meets or exceeds all OSHA requirements. Ships knockdown, some assembly required.

KEY FEATURES

- Great for condensed work areas
- Treaded step design for sure footing
- Collapsible handrail
- Attached casters provide simple maneuvering

CORE PRODUCT DATA

ASSEMBLED WEIGHT
254 lbs

ASSEMBLED SIZE
32.25" W x 42.25" L x 91.625" H

SHIP WEIGHT
274 lbs

PACKAGE 1 SIZE
36" W x 84" D x 19" H

COLOR / FINISH
Blue / Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	350
Incline Angle (degree)	58
Mezzanine Height (in.)	60
Step Height Spacing (in.)	8-5/8
Step Depth (in.)	7
Usable Step Width (in.)	24-1/4
Collapsed Length (in.)	14-5/8
Handrail Height (in.)	31-5/8
Step Material	Serrated Steel
Wheel Quantity/Diameter/Width (in.)	(2) 4 x 1-1/4
Wheel Type	Poly-on-Poly
Overall Width (in.)	32-1/4
Extended Length (in.)	42-1/4

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA