

# Steel Maintenance Ladder 58 Degree 2 Perforated 24 In. Step Width 350 Lb. Capacity Yellow

**MODEL LAD-MM-2-P-YL**

Industrial Ladders / Maintenance Ladders



## PRODUCT OVERVIEW

Portable maintenance ladder for use around a variety of stores and inventory rooms. Constructed of square tubing framework, which handles uniform capacities up to 350 lbs. hand railing provides user safety while ascending or descending the unit. Distance between steps is 10". Powder coated finish for baked in added toughness.

## KEY FEATURES

- Complies with ANSI 14.7 and OSHA 1910.29 specifications
- Portable ladder allows workers to easily maneuver throughout the warehouse
- Simple tilt back design allows for easy portability
- Removable access chain increases worker safety when not in use

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**69 lbs**

**ASSEMBLED SIZE**  
**29.5" W x 38.5" L x 50" H**

**SHIP WEIGHT**  
**110 lbs**

**PACKAGE 1 SIZE**  
**40" W x 48" D x 36" H**

**COLOR / FINISH**  
**Yellow**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                     |               |
|-------------------------------------|---------------|
| Uniform Capacity (lb.)              | 350           |
| Step Angle (degrees)                | 58            |
| Step (qty.)                         | 2             |
| Top Step Height (in.)               | 20            |
| Hand Rail Height (in.)              | 30            |
| Top Platform Length (in.)           | 21            |
| Top Platform Width (in.)            | 24            |
| Safety Chain (in.)                  | 3/16          |
| Step Width (in.)                    | 24            |
| Step Depth (in.)                    | 7             |
| Step Spacing (in.)                  | 10            |
| Wheel Quantity/Diameter/Width (in.) | (2) 4 x 1-1/4 |
| Wheel Type                          | Poly-on-Poly  |
| Step Style                          | Perforated    |
| OSHA                                | 1910.29       |
| ANSI                                | A14.7         |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA