

Steel Orbit Non Telescoping Lift Boom 24 In. Fork Pocket Center 4,000 Lb. Capacity Blue

MODEL LM-OBNT-4-24

Fork Truck Attachments / Orbiting Fork Truck Booms



PRODUCT OVERVIEW

The non-telescoping orbit lift boom delivers heavy-duty performance, maximum operator convenience, and uncompromising safety in challenging manufacturing and warehouse environments. Fabricated from high-strength structural steel and welded to rigorous AWS standards, this rugged, durable unit is engineered for years of reliable, long-term service. For precision operation, it features a locking detent and safety restraint that secures the boom directly to the fork truck to ensure secure, slip-free performance. Ready for immediate use, each unit comes fully equipped with two high-capacity lifting hooks to maximize your facility's material handling efficiency.

KEY FEATURES

- Unique design converts fork trucks into overhead lifting cranes
- Fork pockets with safety strap attach & secure boom to fork truck
- Robotically welded construction provides precision and durability
- Operations & capacity sticker provide user instructions and safety

CORE PRODUCT DATA

ASSEMBLED WEIGHT
337 lbs

ASSEMBLED SIZE
32" W x 80.875" L x 26.625" H

SHIP WEIGHT
337 lbs

PACKAGE 1 SIZE
32" W x 83" D x 27" H

COLOR / FINISH
Blue

FREIGHT TYPE
LTL Loose

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	4,000
Fork Pocket Center (in.)	24
Fork Pocket Size (in.)	7-1/2 x 2-1/2
Restraint Length (in.)	36
Boom Style	Non-Telescoping
Minimum/Maximum Hook Point (in.)	36/78
Single-Hook Capacity at 36" (lb.)	4,000
Single-Hook Capacity at 48" (lb.)	3,750
Single-Hook Capacity at 60" (lb.)	3,500
Single-Hook Capacity at 72" (lb.)	3,250
Single-Hook Capacity at 78" (lb.)	3,000
Overall Max Tilted Height (in.)	57-3/16
Retracted Hook Height (in.)	5-1/2
Max Tilted Hook Height (in.)	38-1/4
Maximum Tilt Degree	37
Boom Type	Orbit Boom
OSHA	1910.178(a)(4)

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA