

Steel Portable Pallet Inverter With Cage 32 In. to 76 In Fork Opening 3,000 Lb. Capacity Yellow/Black

MODEL PI-P-SL-3276-PRSR

Ergonomic Solutions / Portable Pallet Inverters

PRODUCT OVERVIEW

Tilt (powered) and rotate (manual) loads with our durable pallet inverter. Low profile design allows the operator to stand on the rider platform and steer the load from workstation to workstation quickly and easily. DC power lift and drive makes operation safe and efficient. The ergonomic handle features easy to operate throttle and tilt/lower controls. Features an electromagnetic disc brake with automatic dead-man feature that activates when user releases handle. Includes (4) 6V batteries, emergency battery disconnect, and horn. Ideal in loading dock areas as a powered pallet truck, powered pallet tilter, or as a manual turntable. Rolls smoothly on polyurethane steer and load wheels.

KEY FEATURES

- Safety belly reverse button
- On-board battery charger and level gauge
- Steel mesh sides for safe enclosure
- Infinite forward and reverse speeds

CORE PRODUCT DATA

ASSEMBLED WEIGHT
3463 lbs

ASSEMBLED SIZE
56.625" W x 113" L x 108.25" H

SHIP WEIGHT
5400 lbs

PACKAGE 1 SIZE
68" W x 108" D x 86" H

COLOR / FINISH
Yellow / Black

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: --

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	3,000
Fork Opening (in.)	32 to 76
Fork Width (in.)	5
Fork Size (in.)	22 x 42-1/8
Lowered Height (in.)	3-1/4
Turn Radius (in.)	84-1/2
Fork Center (in.)	17-9/16
Caster Material	Poly-on-Steel
Caster Color	Yellow
Stabilizer Caster Quantity/Size (in.)	(2) 5 x 2
Driver Caster Quantity/Size (in.)	(1) 9-7/8 x 3-1/8
Load Roller Quantity	(2) 6-1/4 x 2-3/8
Handle Height (in.)	5-3/16
Handle Diameter (in.)	1-1/8
Hardware Included	No
For Use With	Pallets & Skids
Travel Speed - Unloaded (MPH)	3.7
Travel Speed - Loaded (MPH)	2.5
Drive Motor	24V / 1.2 KW
Lift Motor	24V / 2.0 KW
Battery	4 -6 V / 200 Ah
Battery Charger	24V
Control	Hand Control w/ Coil Cord
Battery Depth	22
Battery Width	21
Battery Height	11
Battery Weight	248
Battery Freight Class	70

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA