

Molded Rubber Wheel Chock with Handle 7-3/8 In. x 15-1/2 In. x 4-7/8 In. Black

MODEL RWC-10-HDL

Loading Dock Equipment / Rubber Wheel Chocks



PRODUCT OVERVIEW

The rubber Wheel Chock with positioning handle is constructed of reinforced rubber to provide a sure grip on virtually any surface. Rubber resists tearing, abrasion, ozone weathering, etc. The functional design is durable in all weather conditions.

KEY FEATURES

- Rubber wheel chock with positioning handle is for ideal operation
- Constructed of reinforced rubber to provide a sure grip on any surface
- Rubber resists tearing, abrasion, ozone weathering, etc
- Functional design is durable in all weather conditions

CORE PRODUCT DATA

ASSEMBLED WEIGHT
12 lbs

ASSEMBLED SIZE
15.5" W x 7.375" L x 4.875" H

SHIP WEIGHT
12 lbs

PACKAGE 1 SIZE
8" W x 11" D x 12" H

COLOR / FINISH
Black

FREIGHT TYPE
Parcel

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Wheel Chock Connection	None
Wheel Chock Usage	Multi-Purpose
Built-In Handles / Poles	Yes
Grip Surface Material	Rubber
Wheel Chock Quantity	1
Usable Chock Width (in.)	9-1/2
Handle Hole Diameter (in.)	1/2
Handle Length (in.)	5-5/8

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 30 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA