

Steel Counter Balanced Powered Drive Lift 2 In. to 118 In. Raised Height 1,000 Lb. Capacity Black / Yellow

MODEL S-CB-118

Ergonomic Solutions / Counter-Balanced Powered Drive Lifts



PRODUCT OVERVIEW

The counter-balanced power drive lift is ideal for die loading, machine feeding, and for loading and unloading trucks. The high torque drive and lift motor handles heavy-duty jobs. The ergonomic handle features an easy-to-operate throttle with infinite adjustment of forward and reverse speeds, lift/lower controls, proprietary safety-enhancing emergency reverse function, and horn. When the proprietary safety-enhancing emergency reverse function is actuated, the emergency reverse belly switch instantly reverses direction and moves the unit forward (away from the operator) until the switch is released or after five (5) seconds have elapsed. The built-in safety circuit will automatically disable the entire unit if the emergency reverse belly switch is...

KEY FEATURES

- Fully-powered pallet truck makes movement of pallets quick and easy
- Includes fingertip raise and lower buttons for operator convenience
- Safety belly reverse button improves worker safety
- Easy-to-operate throttle for forward and reverse direction

CORE PRODUCT DATA

ASSEMBLED WEIGHT
1832 lbs

ASSEMBLED SIZE
32.25" W x 85" L x 78" H

SHIP WEIGHT
2140 lbs

PACKAGE 1 SIZE
46" W x 96" D x 85" H

COLOR / FINISH
Black / Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: YES

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Capacity at 0 - 62" (lb.)	1,000
Uniform Capacity at 62 - 118" (lb.)	500
Service Range (in.)	2 to 118
Fork Width/Length (in.)	3-1/8 x 30
Adjustable Fork Spacing (in.)	6-1/4 to 23-1/2
Overall Mast Height (in.)	78
Drive Motor	24V / 0.7 KW
Lift Motor	24V / 2 KW
Operation Time with Constant Use (hrs.)	3 to 4
Operation Time with Intermittent Use (hrs.)	8
Time to Raise - Unloaded (sec.)	16
Time to Raise - Loaded (sec.)	19
Time to Lower - Unloaded (sec.)	33
Time to Lower - Loaded (sec.)	31
Battery Depth	11
Battery Width	14
Battery Height	9
Battery Weight	84
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA