

# Steel Auto Hite Cart 49-1/8 In. x 20-7/16 In. x 37-11/16 In. 750 Lb. Capacity Blue

**MODEL SCSC-750-2040**

Ergonomic Solutions / Auto-Hite Carts



## PRODUCT OVERVIEW

The auto-Hite cart raises and lowers as materials are removed or added to the platform, keeping material at an ergonomic work height. It increases efficiency while reducing potentially harmful bending and twisting motions. Carts utilize tension springs which can be adjusted in order to fit each particular application. The unit has an all steel construction with a removable handle and rolls smoothly on polyurethane casters, two (2) rigid, and two (2) swivel with brake.

## KEY FEATURES

- Platform automatically moves down as weight is added and up as weight is removed for correct ergonomic heights
- Simple adjustable spring tension is variable for use with different types of loads
- Removable handle allows for simple loading and unloading
- Increases efficiency while reducing potentially harmful bending and twisting motions

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**276 lbs**

**ASSEMBLED SIZE**  
**20.4375" W x 49.125" L x 37.6875" H**

**SHIP WEIGHT**  
**320 lbs**

**PACKAGE 1 SIZE**  
**41" W x 49" D x 39" H**

**COLOR / FINISH**  
**Blue**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                      |                                 |
|--------------------------------------|---------------------------------|
| Uniform Capacity (lb.)               | 750                             |
| Platform Width (in.)                 | 20-3/8                          |
| Platform Length (in.)                | 40-3/8                          |
| Lowered Height (in.)                 | 14                              |
| Raised Height (in.)                  | 34                              |
| Springs (qty.)                       | 3                               |
| Spring Rate                          | 38 lb. per inch                 |
| Caster Quantity/Diameter/Width (in.) | (4) 5 x 2                       |
| Caster Type                          | (2) Rigid (2) Swivel with Brake |
| Caster Material                      | Polyurethane                    |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA