

Steel Dock Safety Swing Gate 9 Ft. Length White

MODEL SSG-9-WT

Loading Dock Equipment / Economical Safety Swing Gates

PRODUCT OVERVIEW

Economical safety swing gates are an economical way to protect people from dock falls. Durable railings are constructed from schedule 10 pipe (1-5/8" O.D.). Units have a top rail height of 46-1/4" and a 25" mid-rail. 4" poly-on-poly wheel allows units to be swung out of the way. Cast single socket is included.

KEY FEATURES

- Ideal for loading docks, floor openings, and mezzanines
- Pre-drilled base plate mounting holes
- White powder coat finish
- Foot release lock keeps railing from moving when in use

CORE PRODUCT DATA

ASSEMBLED WEIGHT
58.67 lbs

ASSEMBLED SIZE
6.5" W x 108.0625" L x 46.25" H

SHIP WEIGHT
84 lbs

PACKAGE 1 SIZE
44" W x 120" D x 8" H

COLOR / FINISH
White

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: --

PRODUCT SPECIFICATIONS

Hardware Included	Yes
Base Plate Mounting Hole Qty	4
Base Plate LxW (in.)	4-1/2 x 4-1/2
Base Plate Mounting Hole Diameter (in.)	3/8
Base Plate Thickness (in.)	1/4
Handrail LxH (in.)	108 x 46-1/4
Midrail Height (in.)	25-3/4
Rigid Caster (qty.)	1
Rigid Caster Diameter (in.)	4
Rigid Caster Width (in.)	1-1/4
Caster Material	Polyurethane
Caster Color	Black

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA