

PVC Vinyl Strip Door Clear Rib Material 150 Ft.

MODEL TG-1200-ROLL-RIB

Loading Dock Equipment / Vinyl Strip Doors

Product image unavailable

PRODUCT OVERVIEW

Vinyl strip doors help control noise, dust, fumes, and smoke while minimizing drafts, reducing illnesses, and accidents. The strip doors offer visual clarity without sacrificing safety. The material design also deters UV rays during direct sunlight when applied to loading docks and external doorways. The simple low cost design is easy to maintain, while reducing heating and cooling costs. All doors are shipped pre-assembled and ready for installation. Installation hardware not included.

KEY FEATURES

- Vinyl strip design helps to minimize heating and cooling costs
- Minimizes UV rays
- Maintains visibility of area
- Design allows user to comfortably enter & exit

CORE PRODUCT DATA

ASSEMBLED WEIGHT
128 lbs

ASSEMBLED SIZE
12" W x .12" L x 1800" H

SHIP WEIGHT
164 lbs

PACKAGE 1 SIZE
30" W x 36" D x 18" H

COLOR / FINISH
Clear

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Roll Length (ft.)	150
Tensile Strength (PSI)	2635
Maximum Tensile Elongation (percent)	388
Graves Tear Load (lb.)	35.4
Graves Tear Extension (in.)	2.07
Load at 100% Elongation (lbs.)	32.2
Strength at 100% Elongation (PSI)	1181
Stiffness in Flexure - 23 degrees Celsius (PSI)	1805
Brittleness Temperature by Impact (degrees Celsius)	35
Recommended Operating Temperature - Range (degrees Celsius)	-10 to 140
Specific Gravity	1.22
Haze Transmittance (percent)	6.30
Luminous Transmittance (percent)	82.80

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA