

Steel Tilt Master DC Powered 12 Volt 6,000 Lb. Capacity Blue

MODEL TM-60-DC

Ergonomic Solutions / Tilt Master & Tilt Master Straddle



PRODUCT OVERVIEW

The tilt master lifts and positions filled tote boxes or baskets without the need of a fork truck or lift table using the newly designed heavy-duty tilt master. The tilter will function as transporters by moving completed products from work station to work station without waiting for a fork truck. This lift has a thin profile to allow the user to get as close to the load as possible, a standard floor lock and rolls easily on the phenolic steering wheels. It is designed to be used with open bottom pallets or skids. The unit is powered by an electric DC motor that includes, standard, an on-board battery charger and battery charge indicator.

KEY FEATURES

- Folding ergonomic handle
- Two rigid and two swivel casters provide smooth and efficient mobility
- 90 Degrees tilt angle allows for better ergonomic access
- Push button hand control for quick lifting and lowering

CORE PRODUCT DATA

ASSEMBLED WEIGHT
717 lbs

ASSEMBLED SIZE
41.0625" W x 75.1875" L x 28.625" H

SHIP WEIGHT
753 lbs

PACKAGE 1 SIZE
40" W x 64" D x 35" H

COLOR / FINISH
Blue

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: --

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	6,000
Fixed Fork Spacing (in.)	27
Operator Reach (in.)	7-1/4
Fork Width with Stiffener (in.)	6-1/2
Fork Length (in.)	38-1/16
Fully Rotated Fork Height (in.)	76-5/16
Lowered Fork Height (in.)	3-1/2
Maximum Tilt Degree	90
Power	12V DC
Wheel Diameter (in.)	8
Wheel Width (in.)	3
Wheel Type	Phenolic
Folding Handle Length (in.)	20
Load Center (in.)	20
Level Height (in.)	28-5/8
Fully Rotated Mast Height (in.)	33
Battery Depth	11
Battery Width	7
Battery Height	9
Battery Weight	42
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA