

Polyurethane Wheel Chock 15 In. x 22 In. x 10 In. Tire Overall Depth 142 In. 255 Ton Capacity Yellow

MODEL URWC-HD-24

Loading Dock Equipment / Urethane Wheel Chocks

PRODUCT OVERVIEW

When it comes to maintaining strength and stability look no further than the polyurethane wheel chock. With a wide foundational base the chock can keep loads of many sizes safe and secure from movement or jostling. A handle is included in the back for easy carrying and transference from place to place, while there are pre drilled mounting holes if the location is more permanent. The bright color encourages clear visibility and awareness.

KEY FEATURES

- Polyurethane construction for continued durability
- Built in bar style handle for simple grasping and carrying
- Large capacity to handle a variety of load sizes
- Resistant to a variety of chemicals

CORE PRODUCT DATA

ASSEMBLED WEIGHT
24 lbs

ASSEMBLED SIZE
15" W x 22" L x 10" H

SHIP WEIGHT
25 lbs

PACKAGE 1 SIZE
16" W x 23" D x 11" H

COLOR / FINISH
Yellow

FREIGHT TYPE
Parcel

AVAILABILITY Quote Required - Please Contact Sales

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Capacity (tons) GVWR	255
Fits Tire Size (in.)	Up to 142

PRODUCT & SHIPPING REFERENCE

Shipping Point: Henderson, CO 80640

Warranty: 30 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA