

Polyurethane Wheel Chock 7-1/2 In. x 6-9/10 In. x 8-1/2 In. Tire Overall Depth 35 In.15 Ton Capacity Orange

MODEL URWC-SW-2

Loading Dock Equipment / Urethane Wheel Chocks

PRODUCT OVERVIEW

A polyurethane wheel chock is the perfect asset for maintaining wheel stability. With a sturdy foundational base the chock can keep loads of many sizes safe and secure from movement or jostling. A handle is included in the back for easy carrying and transference from place to place, while there are pre drilled mounting holes if the location is more permanent. The bright color encourages clear visibility and awareness.

KEY FEATURES

- Polyurethane construction for continued durability
- Lightweight for simple grasping and carrying
- Large capacity to handle a variety of load sizes
- Brightly colored for clear visibility



CORE PRODUCT DATA

ASSEMBLED WEIGHT
2.2 lbs

ASSEMBLED SIZE
6.9" W x 8.5" L x 7.5" H

SHIP WEIGHT
4 lbs

PACKAGE 1 SIZE
9" W x 10" D x 8" H

COLOR / FINISH
Orange

FREIGHT TYPE
Parcel

AVAILABILITY Quote Required - Please Contact Sales

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: --

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Capacity (tons) GVWR	15
Fits Tire Size (in.)	Up to 35

PRODUCT & SHIPPING REFERENCE

Shipping Point: Henderson, CO 80640

Warranty: 30 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA