

# Steel Stacker with Adjustable Forks/Legs DC Powered Winch 770 Lb. Capacity Black / Yellow

**MODEL VWS-770-AA-DC**

Ergonomic Solutions / Manual & Electric Stackers



## PRODUCT OVERVIEW

The electric winch stacker features a heavy duty mast and a DC winch for easier and safer lifting. Lift and lower by DC winch and steel cable mechanism. A full height push-handle is included for easy steering and excellent visibility through welded mesh guard. The unit rolls smoothly on two rigid and two swivel wheels with brakes for easy maneuvering.

## KEY FEATURES

- Adjustable forks for full grasp
- Ergonomic handle for full posture transferring
- DC operated for constant power supply
- (2) 12V batteries

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
492 lbs

**ASSEMBLED SIZE**  
45" W x 48" L x 78" H

**SHIP WEIGHT**  
566 lbs

**PACKAGE 1 SIZE**  
45" W x 64" D x 85" H

**COLOR / FINISH**  
Black / Yellow

**FREIGHT TYPE**  
LTL Palletized

**AVAILABILITY** Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

|                                            |                        |
|--------------------------------------------|------------------------|
| Uniform Capacity (lb.)                     | 770                    |
| Service Range (in.)                        | 1-9/16 to 63           |
| Fork Length (in.)                          | 30                     |
| Fork Width (in.)                           | 3-1/8                  |
| Leg Width (in.)                            | 2-3/8                  |
| Adjustable Straddle Leg Spacing (in.)      | 40-1/8 to 50 (ID)      |
| Adjustable Fork Spacing (in.)              | 6-1/4 to 19-11/16 (OD) |
| Operation                                  | DC Winch               |
| Lift Motor                                 | DC 12V / 120 W         |
| Battery Quantity/Volts                     | (2) 12V / 40-60 Ah     |
| Battery Charger                            | 12V / 8 Ah             |
| Lifting Speed w/ Load (sec.)               | 3.35                   |
| Lifting Speed w/o Load (sec.)              | 4.34                   |
| Rear Caster Quantity/Diameter/Width (in.)  | (2) 6 x 1-1/2          |
| Rear Caster Material                       | Phenolic               |
| Front Caster Quantity/Diameter/Width (in.) | (2) 4 x 1-1/2          |
| Front Caster Material                      | Phenolic               |
| Horizontal Load Center (in.)               | 24                     |
| Battery Depth                              | 8                      |
| Battery Width                              | 7                      |
| Battery Height                             | 7                      |
| Battery Weight                             | 28                     |
| Battery Freight Class                      | 60                     |
| Battery NMFC Number                        | 60700                  |
| Battery NMFC Description                   | Gel batteries on unit  |
| Lithium Battery Configuration              | C -- Contained In      |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA