

Galvanized Steel AC Powered Jib Crane CSA Compliant 3-5 Ft. Boom 2,000 Lb. Capacity Gray

MODEL WTJ-20-3-AC-CSA-GAL

Overhead Lifting / Power Lift Jib Cranes



PRODUCT OVERVIEW

The power lift Jib cranes are designed for material handling applications on docks, in warehouses or in truck beds. Choose either 12V DC, 1 HP with 6-foot long removable pendant control or 115V AC 1/3 HP with fingertip switch to raise and lower hook. Meets ANSI and OSHA specifications. 12" x 12" mounting plate. Units are not rated for overhead lifting applications. Consult factory for pricing if overhead lifting rating is required. Intermittent use cranes feature rotation hand brakes that offer unlimited 360 degrees positioning. Mast mounts permanently. Boom adjusts in 12" increments and can be positioned at 4 elevations. The AC units feature 25 feet of 7/32" cable. Folds for storage.

KEY FEATURES

- Powered cable winch makes lifting and maneuvering easy
- Boom telescopes in and out for greater reach and versatility
- 360 Degrees swivel design allows for maximum accessibility
- Pre-drilled base plate makes mounting quick and easy

CORE PRODUCT DATA

ASSEMBLED WEIGHT
275 lbs

ASSEMBLED SIZE
18.6875" W x 63.5" L x 73" H

SHIP WEIGHT
284 lbs

PACKAGE 1 SIZE
30" W x 67" D x 18" H

COLOR / FINISH
Gray

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	2000
Boom Reach (in.)	39-1/4 to 63-1/4
Boom Height (in.)	59-9/16 to 96-1/8
Rotation Degree	360
Boom Adjustment Increments (in.)	12
Cable Length (ft.)	25
Cable Diameter (in.)	7/32
AC (volts)	115
Horsepower (HP)	1/3
Mounting Plate Length (in.)	12
Mounting Plate Width (in.)	12
Capacity at 59-9/16" Fully Retracted (lbs.)	650
Capacity at 59-9/16" Mid-Position (lbs.)	400
Capacity at 59-9/16" Fully Extended (lbs.)	250
Capacity at 74-1/4" Fully Retracted (lbs.)	1,000
Capacity at 74-1/4" Mid-Position (lbs.)	770
Capacity at 74-1/4" Fully Extended (lbs.)	600
Capacity at 86-13/16" Fully Retracted (lbs.)	1,250
Capacity at 86-13/16" Mid-Position (lbs.)	950
Capacity at 86-13/16" Fully Extended (lbs.)	780
Capacity at 96-1/8" Fully Retracted (lbs.)	2,000
Capacity at 96-1/8" Mid-Position (lbs.)	1,500
Capacity at 96-1/8" Fully Extended (lbs.)	1,200
Compliant	CSA

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA